

ULL Series Red Laser Line Module

Part No: ULL5-3.5P-905-45




Product Features

- High Stability and low noise
- Collimated or Adjustable focus beam
- Reverse Polarity Protection
- Custom Options Available

Application

- Measurement
- Bioanalytical
- Automation
- Alignment

Mechanical Drawing



Specification

| OPTICAL | |
|-------------------------------------|-----------------------|
| Wavelength | 905 nm |
| Optical Output Power | 3.5 mW |
| Stability | <1% |
| Laser Class | IIIb |
| Wavelength Drift | 0.2nm/°C |
| Noise (20MHz Bandwidth) | <0.5% RMS |
| Laser Operation | Continuous |
| Laser Structure | Single Mode Laser |
| Line Thickness | Uniform, Fixed Focus |
| Minimum Line Thickness | < 2mm up to 1.5 meter |
| Pointing Stability | <50μrad |
| ELECTRICAL | |
| Operating Voltage ¹ | 3 to 5 VDC |
| Operating Current | <60 mA |
| Control Circuit | Auto Power Control |
| Electrical Connections | +Red, -Black |
| MECHANICAL | |
| Dimension (Dia * Length) | 10.5mm * 24mm |
| Cable | 380mm |
| Operating Temperature | -10°C to +50°C |
| Storage Temperature | -40°C to +80°C |
| Heat Sink Requirements ² | Recommended |

Notes

1. Higher operating voltage version (9 to 12V) is available, the part No. will be: ULL12-3.5P-905-45.

2. Heat Sink: The ULL Series Red Laser Line Module is designed to operate without heat sink. Do not restrict air circulation around the device; an additional heat sink can be used to maximize the performance and life time of the laser.

Caution: The case is internally connected to the circuit; damage to the anodized surface may result in failure of the laser module.



Sold for OEM use only. OEM responsible for compliance with all applicable safety regulations.

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

World Star Tech.

321 Lesmill Rd. Toronto, Ont. M3B 2V1 Canada
Tel: (416) 363-3332 Fax: (416) 363-3112 www.worldstartech.com

Rev.6 Jun.2005