



DATASHEET



FEATURES

- ✓ Integrated TEC and Laser Controller
- ✓ Excellent Power & Wavelength Stability
- ✓ Low RMS Noise
- ✓ Compact Package

APPLICATIONS

- ✓ Measurement
- ✓ Bioanalytical
- ✓ Confocal Microscopy

Operational Hazard of Laser Module

This laser module emits radiation that is visible/invisible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.



Limited Warranty

One year. No warranty coverage for disassembly, modifications, or damage due to abuse or misapplication.



TECBL Series Thermoelectrically Cooled Laser is a compact, self-contained, highly reliable laser operating at a very stable wavelength and power. The built-in temperature controller stabilizes the laser temperature within $\pm 0.01^\circ\text{C}$. The laser output stability is $<1\%$ over the long term. Extremely stable power, low noise and excellent beam pointing stability of this laser makes it ideal for bioanalytical, measurement and imaging applications.

TECBL Series lasers are provided with a power supply for plug and play operation

TECBL Series lasers can be customized to add beam shaping optics, external modulation and multimode fibers

SPECIFICATIONS

OPTICAL

Wavelength	488 \pm 3 nm
Optical Output Power	5-40 mW
Laser Structure	Single Mode
Laser Power Stability	$<0.5\%$
Laser RMS Noise	$<0.5\%$
Polarization Ratio	100:1
Collimated Beam Size	3mm (typical, may vary with diode)
Beam Shape	Elliptical
Divergence (full angle)	< 1 mrad
Warm-Up time	<1 min

ELECTRICAL


Operating Voltage	3.3 V DC (power supply provided)
Operating Current	< 1.2 A
Control Circuit	APC/ACC depending on power

MECHANICAL

Dimension, mm	25.4(D) \times 76.2(L)
Operating Temperature	$+10^\circ\text{C}$ to $+40^\circ\text{C}$
Storage Temperature	-40°C to $+80^\circ\text{C}$
Heat Sink	Recommended for extended use

DATASHEET

OUTLINE DRAWING



TECBL ORDERING INFORMATION

PART# TECBL-pppG(c)-λλλ

OPTION	DESCRIPTION	VALUES
ppp	Laser output power (mW)	1-150 (depending on wavelength)
(c)	Circular laser diode beam (optional)	C
λλλ	Wavelength (nm)	375, 405, 450, 473, 488
TTL	External TTL Modulation	3 KHz

Example Part # for 30 mW, standard elliptical beam, 488 nm laser: TECBL-30G-488